

Parallel Print Server

Product Images



Short Description

Parallel Printer Server für gemeinsame Druckernutzung im Netzwerk Einfaches Einrichten über benutzerfreundliche Oberfläche Unterstützt verschiedene Netzwerk-Druckprotokolle Unterstützt verschiedene Betriebssysteme

Description

Product Overview The LevelOne FPS-1031 print server is an ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing over the same network. This print server is equipped with a 10/100Mbps autosensing Ethernet port and a DB-36-pin male bi-directional Centronic port that connects to parallel printers.

Multi OS and Network Printing Protocol Support The FPS-1031 is a print server with 1 parallel port that supports Windows ME, 2000, XP and Vista operating systems as well as Mac OS 8.1 and higher, UNIX/Linux and Netware (Bindery/NDS). Network Protocol supported includes TCP/IP, IPX, NetBEUI, AppleTalk, LPR and SMB over TCP/IP for flexible use with different network clients connected to the same office network. The FPS-1031 also includes Internet Printing Protocol (IPP) support and Windows Print Monitor Technology to monitor printing jobs received.

Easy Installation Wizard The LevelOne FPS-1031 is easily configurable using a Web Browser or the Windows based configuration program included with the CD-ROM. The print server is easily managed through a Web based user interface and the firmware is upgradeable through TFTP, the Windows set-up program or the Web based user interface.

Additional Information

Fast-Ethernet RJ45	1
Parallel	D-sub 25-pins Female
Code des Harmonisierten Systems (HS)	851762
Zolltariflicher Warencode (TARIC)	8517620000
Features.	Network Print Protocol Support : LPR,RAW, TCP, IPP, SMB, AppleTalk Netware Bindery/NDS, Print Monitor, Bonjour printing
Printer Interface.	Parallel
Indikator	Power LAN
Stromversorgung	Power adapter
Power supply included.	Ja
Arbeitsspeichergröße	2Mbytes SDRAM
Standards	IEEE 802.3, 802.3u Ethernet Standards
Zulassungen und Konformität	CE, FCC, RoHS
Operating humidity.	0% RH ~ 70% RH
Operating temperature.	0°C ~ 50°C
Unterstützte Betriebssysteme	Windows ME/2000/XP/Vista Mac OS 8.1 and higher UNIX/Linux and Netware (Bindery/NDS).
Storage humidity.	0% RH ~ 80% RH
Storage temperature.	-5°C ~ 65°C
Lieferumfang	FPS-1031 Netzadapter Quick Installation Guide Ressource CD (Bedienungsanleitung, Hilfsprogramm, Treiber)
Farbe	Schwarz
EAN	4015867142226
Modellnummer	FPS-1031
Dimensions (W x D x H).	55 x 51 x 25 mm
Produktgewicht (kg)	0,56

