

NOTES:

ELECTRICAL:


1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN



ENVIRONMENTAL:

1. STORAGE:-40° TO+85°
2. OPERATION:0° TO70°

MECHANICAL:

1. PLASTIC HOUSING MATERIAL: PC
2. INSERT MATERIAL:FAME RETARDANCY ABS
3. PCB MATERIAL:FR-4 T=1.6mm
4. CONTACT MATERIAL:PHOSPHOR BRONZE
STAMP PIN T=0.30mm
5. RJ45 JACK ;IFE:750 TIMES MIN
6. SHIELD MATERIAL: CU-H62, T=0.25mm



											
					Material					Item No.	125590
SYM	Number	Bill No. of Alteration	Signature	Date	Angles Projection		Size	Scale	Unit	Part Name	Cat.6 Shielded Keystone Inline Coupler
							A4	X:1	mm		
Drawn	Ding jian bo	2022.05.16	Tolerance				A4	X:1	mm	ERP	Part No.
Checked	Ge pei jun	2022.05.16	0.00-20.00 ±0.10 20.00-50.00 ±0.15 50.00-100.00 ±0.20								
Approved	Wang wei jun	2022.05.16	100.00-Angle ±0.25 ±30°								