

- 1. Plug: JT006A/JT-ST3 Clear injection no scrath and dirt;
- 2. Cable: H05VV-F 3G0. 75mm² Jacket \(\phi 6.5 \pm 0.2 \) Conductor 24*0. 198\(\pm 0.004 \) Core\(\phi 2.4 \pm 0.1 \) Cable Mark: ≺VDE > H05VV-F 3GO. 75mm² ★ ZHEJIANG JINTING NUCLEAR CABLE CO., LTD
- 3. Test:Hi-pot:lnner Voltage AC2500V/1S External Voltage AC4000V/1S current leakage 1mA, insulation resistance no less than $5M\Omega$, no strike out;

除非另有说明。否则公差按下表。 TELERANCE ACCURSING TO THE FURN . UNLESS OTHERVISE INSECATES			第三角度投影 THE THERD ANGLE PREJECTION			ightharpoons	第X张 共X张				
尺寸标注	公差 TOLERANCE		版本	A Ities		1:1		単位	mm	[B]40,	A4
DIMENSION	长度 LENGTH	角度 MGLE	VERSION	А_	PROPORTION		1.1	UNET	mm	HAPE	_ /\4
<200	±0.1	±0.5°	文件位置 FILE LOCATION								
200~500	±0.3		图号				村監材料 RESIN MATERIALS				
500~800	±0.5		FISURE NO.								
<800	±1.0		ME NO.					N A DKAGE			
设计 DESIGN	王结安										
市 核 AUDIT	贺世民	产品 PRODUCTO	名称 OR NAME	112300			equip equip				
技 准 APPREVAL	施建平	TRODUCT	OR WIEL								