

DAC-0105 10Gbps SFP+ Direct Attach Copper Cable, 5m, Twinax

Product Images



Short Description

- Data rates of up to 10Gbps
- Compatible with SFP Multi-Sourcing Agreement (MSA) standards
- Hot-swappable providing non-stop service
- RoHS compliant and Lead Free

Description

The LevelOne DAC-0105 passive SFP+ cable assembly is a high-performance, cost-effective I/O solution for 10G Ethernet and 10G Fibre Channel applications. SFP+ copper modules enable high port density, configurability and utilization at a very low cost. Perfectly suited for virtual stack and trunking applications with the switches of the GTL and GTP series or also for connection to a NAS system.

The DAC-0105 high-speed cable assemblies meet and exceed the industry standard performance and reliability requirements of Gigabit Ethernet and Fiber Channel.

Additional Information

| Harmonized System (HS) code. | 851762 |
|---------------------------------------|--|
| Customs product code (TARIC). | 8517620000 |
| Color. | Silver |
| EAN. | 4015867199091 |
| Model Number. | DAC-0105 |
| Features. | Bit rate support from 1 to 11.3 GBd ● Preterminated twin axial cable ● Hot pluggable ● Low power consumption ● SFP+ housing with enhanced EMI shielding ● Single 3.3V power supply ● AWG26 (American wire gauge) |
| Transceiver Type. | SFP+ DAC |
| Grade. | Commercial |
| Dimensions (W \times D \times H). | 15 x 5140 x 10 mm |
| Product weight (kg). | 0.32 |
| Data rate. | 10 Gbps |
| Approval and Compliance. | CE ● 47 CFR FCC Part 15, Subpart B, Class B ● ICES-003:2016 Issue 6, updated Apr. 2019, Class B ● CISPR 32:2015 + COR1:2016, Class B ● ANSI C63.4:2014 ● AS/NZS CISPR 32: 2015, Class B ● RoHS |
| Operating humidity. | 10% RH ~ 85% RH |
| Operating temperature. | 0°C ~ 70°C |
| Storage temperature. | -40°C ~ 85°C |
| Package Contents. | ● DAC-0105 ● Quick Installation Guide |
| | |

2 9/10/25

