

UPS-2102, Volta Online UPS 2KVA/2000W

Product Images



Short Description

- True double-conversion design with high adaptability to harsh mains conditions.
- Real PF 1 can provide more power in same space High efficiency results in energy saving.
- Adjustable charging current and flexible battery configuration.
- Optimized changing method to expand battery life time.
- Built-in OVCD protection, fan lock detection, over temperature detection, overload warning to enhance the product reliabilit.
- Dot matrix LCD support up to 10 languages for easy installation and service.(Included 8 languages, with 2 additional customizable options).
- Embedded Ethernet port solution provide safe network connection to Cloud which will meet the increasing IoT trend. Mobile APP for monitoring, Support Android/iOS.
- USB HID enable monitoring on UPS without software installation.
- Dry contactor for industrial condition.
- Free Management Software monitor Max to 1000 unit UPS.

Description

The LevelOne Online UPS is the ultimate solution for dependable battery backup in both

home and office settings. With an output power factor of 1.0, this UPS delivers maximum efficiency and performance. Designed for generator compatibility, it provides continuous power even during extended outages. Equipped with a HID-compatible USB connection for seamless device communication and security.

The easybattery replacement feature simplifies maintenance, while the programmable outlet management allows you to tailor power distribution to meet your specific needs. Easy to install and operate, the LevelOne Online UPS provides a reliable and efficient way to protect your systems from power surges and failures, ensuring the uninterrupted operation of your critical equipment. The included rackmount ears support both rack mounting and tower installation, offering flexibility in setup.

Additional Information

Harmonized System (HS) code.	850440
Protection.	Emergency Power Off (EPO) Port
Recharge time.	VAC 220/1.5A, 3h to 90%
Dimensions (W x D x H).	438x445x85.5
Product weight (kg).	23
Alarm.	Battery Mode, Low Battery, Overload, Fault
Battery capacity (mAh).	6 x 12V/7Ah
Battery capacity (Wh).	84
Battery type.	Lead-acid
Battery voltage.	72V
Switches/Buttons.	Power On/Off, Enter, ESC
Display.	LCD Monitor
Number of battery.	6
Port Configuration.	IEC C13 x 8, RJ45 x 1, USB x 1, HDMI x 1 ,RS-232,Terminal block,EBM detect x1
Power input.	VAC 160-300V
Power Output.	VAC200-240,50Hz/60Hz
Power rating.	2000VA
UPS Type.	Online double conversion
Waveform.	Sine wave
Approval and Compliance.	CE/FCC/RoHS/IP20 IEC/EN 61000-4-2 IEC/EN 61000-4-3 IEC/EN 61000-4-4 IEC/EN 61000-4-5
Operating humidity.	0% RH ~ 90% RH
Operating temperature.	0°C ~ 40°C
Package Contents.	USB cable Power cord User Manual Tower feet Rack ears QIG EcDoc
Color.	Black

EAN.

4015867235027

Model Number.

UPS-2102

